VERIFIED
Roofing & Siding

Roofing Catalog 2026

Asphalt shingles · Synthetic slate & shake · Metal · Low-slope · Skylights

The manufacturer product lines we install for homeowners across Macomb, Oakland, St. Clair, Sanilac, Tuscola and Lapeer counties: specs, colors, accessories, warranty highlights and how each one goes on your home.

BRANDS WE INSTALL

Malarkey Roofing Products · Owens Corning · certainteed Saint-Gobain · DaVinci Roofscapes · BRAVA · MULEHIDE · Versico Roofing Systems · VELUX · QE Quality Edge

WELCOME

How we work

Every Verified project starts with facts about your home, not a guess. You get a written, line-by-line proposal you can compare, and the same crew standards on every job.

1

Measured

We measure every roof plane, wall, opening and run of gutter, so quantities on your proposal match your house.

2

Photographed

We photograph existing conditions (decking, flashing, siding, trim, windows) and share what we find.

3

Priced line by line

Materials, accessories and labor are listed item by item. No lump sums, no surprises.

4

Everything included

Tear-off, installation, job-site cleanup and disposal of old material are part of every project.

Service area. Based in Shelby Township, serving Macomb, Oakland, St. Clair, Sanilac, Tuscola and Lapeer counties, with projects up to 150 miles away.

Using this catalog. Each brand page lists product lines, sizes and coverage, color names, matching trims and accessories, warranty highlights and the manufacturer's installation sequence in plain language. Pricing is quoted per project by your Verified rep. Colors are listed by name only. Ask for physical samples, since printed and on-screen colors are not accurate.

Contents

Roofing 3

- Asphalt shingles at a glance 3
- Malarkey 4
- Owens Corning 5
- CertainTeed 6
- Synthetic slate & shake: DaVinci 7
- Synthetic slate & shake: Brava 8
- Metal roofing & Quality Edge accessories 9
- Low-slope TPO & EPDM 10
- VELUX skylights 11

SECTION 01

01 Roofing

Asphalt shingles from three major manufacturers, synthetic slate and shake, metal, low-slope membranes and skylights. Every roof is installed as a complete system: the shingle warranty depends on the parts under it.

Asphalt shingles at a glance

Shingle line	Impact (UL 2218)	Wind coverage	Algae coverage	Notable
Malarkey Highlander AR	Class 3	110 mph std / 130 enhanced	15 yr	10-yr non-prorated
Malarkey Vista AR	Class 4	110 / 130 mph	25 yr	15-yr non-prorated
Malarkey Legacy Scotchgard	Class 4	110 / 130 mph	Limited Lifetime	20-yr non-prorated
Malarkey Windsor Scotchgard	Class 4	110 / 140 mph	Limited Lifetime	Designer, 5 bundles/sq
Owens Corning Duration	Class 3	Up to 160 mph*	25 yr*	SureNail Technology
Owens Corning Duration FLEX	Class 4	Up to 160 mph*	25 yr*	SBS polymer-modified
Owens Corning Duration STORM	Class 4	Up to 160 mph*	25 yr*	Impact-rated Duration
Owens Corning Duration Designer	Class 3	Up to 160 mph*	25 yr*	11 designer colors
CertainTeed Landmark / Landmark Pro	see note	15-yr 110 mph (130 upgrade)	10 yr	10-yr SureStart
CertainTeed Landmark ClimateFlex	Class 4	15-yr 110 mph (130 upgrade)	25 yr StreakFighter	10-yr SureStart

* Owens Corning: 160 mph requires OC component requirements and starter on eaves and rakes; algae coverage requires an approved OC hip & ridge product. No UL 2218 class is listed for standard Landmark / Landmark Pro in the literature we reviewed; choose Landmark ClimateFlex where a Class 4 rating matters. Malarkey enhanced wind requires a Malarkey Certified Contractor and Malarkey accessories.

What goes into every Verified roof

1. **Deck** — Damaged decking repaired or replaced after tear-off.
2. **Ice & water barrier** — Self-adhered membrane at eaves, valleys and penetrations.
3. **Underlayment** — Synthetic underlayment over the rest of the deck.
4. **Drip edge & flashing** — Metal edge at eaves and rakes; walls and chimneys flashed.
5. **Starter** — Manufacturer starter at eaves (and rakes where required).
6. **Field shingles** — Nailed at the specified exposure and nail pattern.
7. **Hip & ridge + ventilation** — Matching cap shingles and balanced intake/exhaust vents.

Michigan homeowners often ask insurers about impact-rated (UL 2218 Class 4) shingles. Ask your insurance agent whether a Class 4 roof affects your premium.

VERIFIED ROOFING & SIDING × MALARKEY

Malarkey architectural shingles

A Good / Better / Best laminate lineup plus the Windsor designer shingle. All carry a Limited Lifetime warranty and Class A fire rating, and differ mainly in impact rating, non-prorated years and algae coverage.

	Highlander AR GOOD	Vista AR BETTER	Legacy Scotchgard BEST	Windsor Scotchgard DESIGNER
Size	13-1/4" × 39"–40"[1]	13-1/4" × 38-7/8"	13-1/4" × 40"	19-1/4" × 38-1/4"
Exposure	5-5/8"	5-5/8"	5-5/8"	5-3/4"
Bundles / shingles per square	—	3 / 66	4 / 64	5 / 65
Impact (UL 2218)	Class 3	Class 4	Class 4	Class 4
Fire	Class A	Class A	Class A	Class A
Non-prorated period	10 yr	15 yr	20 yr	20 yr
Algae warranty	15 yr	25 yr	Limited Lifetime	Limited Lifetime
Wind, standard / enhanced	110 / 130 mph	110 / 130 mph	110 / 130 mph	110 / 140 mph
Construction notes	NEX polymer asphalt	3 laminate bonds, 2 rain seals	+35% tear strength, +19% thickness vs. Good tier	5 laminate bonds, 3 wind seals, book-style install

[1] Highlander length is listed as 39" or 40" depending on the source; confirm on the bundle wrapper.

COLORS · HIGHLANDER, VISTA & LEGACY

Antique Brown · Storm Grey · Natural Wood · Heather · Black Oak · Brilliant Black · Silverwood · Sienna Blend · Weathered Wood Plus

From Malarkey's 2026 regional color chart. Michigan availability and Windsor colors are confirmed at your color selection.

Malarkey roof system (install order)

1. Ice & water	Arctic Seal (SBS rubberized); Secure Start HT (high-temp)
2. Underlayment	Secure Start Lite, Plus or Permeable (synthetic)
3. Starter	Smart Start (Windsor Starter for Windsor)
4. Field shingle	Highlander AR / Vista AR / Legacy / Windsor
5. Hip & ridge	RidgeFlex (low profile) or EZ-Ridge (high profile)

✓ Warranty highlights

- Limited Lifetime material warranty on all four lines.
- Non-prorated coverage: 10 / 15 / 20 / 20 years (Highlander / Vista / Legacy / Windsor).
- 110 mph standard wind; enhanced 130 mph (140 mph Windsor) requires a Malarkey Certified Contractor and Malarkey accessories.
- Algae warranties cover blue-green algae (Gloeocapsa magma) staining.

Installation process

1. Tear off to the deck; repair or replace damaged decking.
2. Install Arctic Seal ice & water barrier at eaves, valleys and penetrations.
3. Cover the rest of the deck with Secure Start synthetic underlayment.
4. Install drip edge and flashings, then Smart Start starter along eaves and rakes.
5. Nail field shingles at the specified exposure with corrosion-resistant nails, never staples (6 nails plus hand-sealing on slopes over 21/12).
6. Cap hips and ridges with RidgeFlex or EZ-Ridge, finish ventilation and clean up.

VERIFIED ROOFING & SIDING × OWENS CORNING

Owens Corning Duration Series

Every Duration Series shingle shares one size and SureNail Technology, a reinforced nailing zone with Triple Layer Protection. Choose by impact rating and color palette.

	Duration	Duration FLEX	Duration STORM	Duration Designer
Size / exposure	13-1/4" × 39-3/8" / 5-5/8"	13-1/4" × 39-3/8" / 5-5/8"	—	13-1/4" × 39-3/8" / 5-5/8"
Bundles / shingles / coverage per sq	3 / 64 / 98.4 sq ft	3 / 64 / 98.4 sq ft	—	3 / 64 / 98.4 sq ft
Impact (UL 2218)	Class 3	Class 4	Class 4	Class 3
Wind	Up to 160 mph*	Up to 160 mph*	Up to 160 mph*	Up to 160 mph*
Algae	25 yr**	25 yr**	25 yr**	25 yr**
Regional colors	21	9	7	11
What sets it apart	The core Duration shingle	SBS "rubberized" asphalt; 42% higher nail-pull resistance, 10%+ higher tear strength	Impact-resistant Duration	Bold designer blends

* 160 mph requires Owens Corning component requirements to be met and starter on both eaves and rakes. ** Algae coverage requires an approved OC hip & ridge product. "—" = not listed in the literature we reviewed.

DURATION · POPULAR COLORS

Brownwood · Desert Rose · Driftwood · Estate Gray · Onyx Black · Sierra Gray · Slatestone Gray · Teak · Williamsburg Gray

A selection of the 21-color regional palette; the full Michigan palette is shown at your color selection.

DURATION FLEX · 9 COLORS

Black Sable · Brownwood · Driftwood · Estate Gray · Onyx Black · Sand Dune · Storm Cloud · Summer Harvest · Teak

DURATION DESIGNER · 11 COLORS

Aged Copper · Black Sable · Bourbon · Evergreen Mist · Gray Tweed · Merlot · Mountain Pine · Pacific Wave · Sand Dune · Sedona Canyon · Summer Harvest

Total Protection Roofing System

Underlayment	Deck Defense synthetic
Ice & water	WeatherLock
Starter	Starter Strip Plus
Field shingle	Duration Series with SureNail
Hip & ridge	ProEdge
Ventilation	VentSure intake and exhaust

✓Warranty highlights

- Limited Lifetime shingle warranty across the Duration Series.
- Wind warranty up to 160 mph when OC component requirements are met, with starter on eaves and rakes.
- 25-year algae-resistance coverage with an approved OC hip & ridge.
- Because both depend on OC accessories, Verified quotes OC starter and hip & ridge with every Duration roof.

Installation process

1. Tear off to the deck; repair or replace damaged decking.
2. Install WeatherLock ice & water barrier at eaves, valleys and penetrations.
3. Cover the deck with Deck Defense synthetic underlayment.
4. Install drip edge and flashings, then Starter Strip Plus on both eaves and rakes.
5. Nail Duration shingles through the SureNail strip at 5-5/8" exposure.
6. Cap hips and ridges with OC hip & ridge, install VentSure ventilation, clean up.

Sequence shown is standard practice using the OC components named above.

VERIFIED ROOFING & SIDING × CERTAINTEED

CertainTeed Landmark Series & luxury shingles

Landmark is CertainTeed's core architectural shingle; Landmark Pro adds weight and Max Def color; Landmark ClimateFlex adds a Class 4 impact rating. Grand Manor and Presidential Shake are the luxury, multi-layer options.

Line	Size	Exposure	Weight / sq	Ratings & notes
Landmark	13-1/4" × 38-3/4"	5-5/8"	229 lb	UL Class A fire; ASTM D3161 Class F wind
Landmark Pro	13-1/4" × 38-3/4"	5-5/8"	270 lb	Heavier, Max Def color blends
Landmark ClimateFlex	—	—	—	UL 2218 Class 4 impact; 25-yr StreakFighter algae
Grand Manor	—	—	about 425 lb	Two-layer laminated, random-tab "super-heavyweight"; D3161 Class F, D7158 Class H, UL 790 Class A
Presidential Shake	14-1/4" × 40"	4"	355 lb	Triple-laminate shake look (TL version 475 lb/sq)

Landmark, Landmark Pro and Presidential weights are from CertainTeed's published product guide (2018) and may have changed slightly. "—" = not listed in the literature we reviewed.

LANDMARK · NORTH CENTRAL COLORS

Burnt Sienna · Cobblestone Gray · Colonial Slate · Driftwood · Georgetown Gray · Heather Blend · Hunter Green · Moiré Black · Pewter · Resawn Shake · Weathered Wood · Silver Birch (limited areas)

LANDMARK PRO · MAX DEF COLORS

Max Def Charcoal Black · Max Def Cobblestone Gray · Max Def Driftwood · Max Def Heather Blend · Max Def Moire Black · Max Def Red Oak · Max Def Resawn Shake

LANDMARK CLIMATEFLEX · 6 COLORS

Weathered Wood · Burnt Sienna · Heather Blend · Resawn Shake · Moiré Black · Colonial Slate

Integrity Roof System components

Waterproofing	WinterGuard, DryRoof SA
Underlayment	DiamondDeck, RoofRunner, RoofRunner AIR
Starter	SwiftStart, High-Performance Starter, Presidential Starter
Hip & ridge	Shadow Ridge, CedarCrest, Mountain Ridge, Shangle Ridge
Ventilation	CertainTeed ridge, intake and soffit vents

✓Warranty highlights

- Landmark Series: Lifetime limited warranty with 10-year SureStart protection (materials and labor).
- 15-year wind coverage at 110 mph; upgrade to 130 mph with CertainTeed starter and hip & ridge.
- Algae resistance: 10 years (Landmark); 25-year StreakFighter (ClimateFlex).
- Landmark ClimateFlex warranty is transferable (lifetime limited).

Installation process

1. Tear off to the deck; repair or replace damaged decking.
2. Install WinterGuard waterproofing underlayment at eaves, valleys and penetrations.
3. Cover the deck with DiamondDeck or RoofRunner synthetic underlayment.
4. Install drip edge and flashings, then SwiftStart starter at eaves and rakes.
5. Nail Landmark shingles at 5-5/8" exposure following the wrapper nailing pattern.
6. Cap with Shadow Ridge or Mountain Ridge, install ventilation, clean up.

Sequence shown is standard practice using the CertainTeed components named above.

VERIFIED ROOFING & SIDING × DAVINCI ROOFSCAPES

DaVinci Roofscapes synthetic slate & shake

Composite slate and shake tiles from Westlake Royal Building Products. Lines: Single-Width Slate, Multi-Width Slate, Province Slate, Inspire Slate, Multi-Width Shake, Single-Width Shake and Select Shake. All are Class 4 impact and Class A fire rated.

	Single-Width Slate	Multi-Width Slate	Shake (Multi-Width, Single-Width, Select)
Tile size	12" × 18"; 1/2" butt tapering to 1/8"	18" long; 6", 7", 9", 10", 12" wide	Profiles 1/4"–5/8" thick
Starter	12" × 12"	12" × 12"	Matching DaVinci starter
Pieces per bundle	10	28	—
Weight	—	342 / 293 / 273 lb per sq at 6" / 7" / 7-1/2" exposure	—
Impact / fire	Class 4 / Class A	Class 4 / Class A	Class 4 / Class A
Wind	110 mph (ASTM D3161)	TAS 125 uplift tested	110 mph; up to 180 mph when fastened per spec

NEW SHAKE COLORS (2025, NATURE CRAFTED COLLECTION)

Timber Black · Blonde Cedar

RECENT SINGLE-WIDTH SLATE COLORS

Rock Ridge · Aurora

COOL ROOF COLORS

Castle Gray · Brownstone

50+ standard slate and shake colors plus pre-sorted blends and custom colors. An optional Renaissance UV finish adds fade protection. Choose from physical samples or the Westlake Royal visualizer.

✓ Warranty highlights

- Lifetime Limited Material Warranty (current Westlake Royal literature).
- Shake: 10-year non-prorated coverage against manufacturing defects.
- Class 4 impact, Class A fire, hurricane wind performance rated.

Installation process

1. Inspect the deck: framing solid, attic ventilation in place, deck clean and dry.
2. Install self-adhered ice & water membrane at eaves (2 ft inside the warm wall line), valleys, walls and penetrations, at 40°F or above.
3. Cover the roof with underlayment and install drip edge and metal flashings, lapped at least 2" and sealed.
4. Lay the starter row, then tiles bottom-up with a 3/16"–3/8" gap. Offset joints at least 1-1/2" and never place matching colors or widths side by side.
5. Fasten each tile with 2 nails (copper, stainless or hot-dip galvanized), flush and not overdriven; keep nails 5" from valley centerlines.
6. Cap hips and ridges with a double row over 6" metal flashing at 6" exposure; add snow guards where snow builds up.
7. Inspect from the ground about every 200 tiles and replace any damaged pieces.

VERIFIED ROOFING & SIDING × BRAVA

Brava Roof Tile composite slate & shake

Thick, deep-profile composite tiles made with recycled content and fully recyclable. Brava offers Old World Slate, Cedar Shake and Spanish Barrel Tile; slate and shake are detailed below.

	Old World Slate	Cedar Shake
Size	22" L × 12" W (multi-width 6", 9", 12"); 1" thick profile	5", 7", 12" nominal widths (5-1/8", 7-1/8", 12-1/8" actual); 5/8"–7/8" thick
Exposure	10"	10" recommended (can be reduced or staggered)
Weight	311 lb per square	355 lb per square
Bundle	10 pcs (12") or 12 pcs (multi-width)	12 pcs (4 of each width)
Impact	Class 4	Class 4
Fire	Class A or Class C depending on version	Class A or Class C depending on version
Wind	Up to 188 mph (ring-shank nails); 211 mph high-wind screw install	110 mph wind-driven rain rating
Accessories	Starter 12" × 12"; solid tile 22-7/8" × 12-1/8"; hip & ridge 16" × 6" × 5-5/8" (90°, 120°, 160°)	Matching starter and hip & ridge

OLD WORLD SLATE · STANDARD COLORS

Arendale · Light Arendale · Atlantic · Cottage · Graphite · Onyx · Washington Slate

OLD WORLD SLATE · PREMIUM COLORS (UP-CHARGE)

European · Pine Green · Tuscan Clay · Victorian · Deep Green · Gray · Welsh

Cedar Shake: available in any color or custom color combination. Choose from Brava samples at your color appointment.

✓ **Warranty highlights**

- Old World Slate: 50-year limited, transferable, with a hail warranty.
- Cedar Shake: 50-year limited.
- Fire rating depends on version and underlayment: confirm the Class A assembly on your quote.

Installation

Brava installs much like DaVinci (see the previous page): ice & water and underlayment, metal flashings, starter row, then tiles set at a 10" exposure and fastened per Brava's installation guide, finished with Brava hip & ridge.

VERIFIED ROOFING & SIDING

Standing seam & exposed-fastener metal roofing

Metal roofing is built for a long service life. We offer two styles, both roll-formed steel panels with factory paint finishes.

Standing seam

- Concealed fasteners: panels lock together at raised seams, so no screws pierce the weather surface.
- Clean, modern lines; the premium metal option.
- Panel profile, width, gauge and color chart are confirmed on your quote from our current panel supplier.

Exposed-fastener panels

- Ribbed panels screwed through the face with sealing-washer fasteners.
- Common on barns, outbuildings, porches and budget-conscious projects.
- Profile, gauge and color confirmed on your quote from our current panel supplier.

Installation process (standing seam)

1. Tear off to the deck; metal panels are not installed over existing shingles. Repair the deck (minimum 1/2" plywood).
2. Install high-temperature ice & water barrier and synthetic underlayment.
3. Install valley, eave, rake and drip-edge flashings before the panels.
4. Cut panels with shears (not abrasive saws, which damage the coating), keeping the factory end intact.
5. Set panels across the roof, seating each seam, and fasten through the nail strip with pancake-head screws.
6. Peel the protective film as each panel goes on, add ridge and trim, then inspect.

Summary of typical manufacturer requirements; the panel maker's current manual governs each job.

VERIFIED ROOFING & SIDING × QUALITY EDGE

Quality Edge trims & roofing accessories

Accessories we use

- Drip edge: T-style, C-style, Siders Edge, asphalt drip, gravel stop, gutter apron (incl. Infinity drip edge).
- Metal valleys and roof flashing.
- Aluminum (about .011"–.024") and steel incl. Galvalume (about .010"–.019").
- Made by Quality Edge in Walker, Michigan.

✓ **Warranty highlights**

- Quality Edge roofing accessories carry a lifetime limited warranty.

QUALITY EDGE "SYSTEM COLORS" FOR DRIP EDGE & TRIM

518 Black · 502 Brown · 807 Clay · 327 Desert Tan · 522 Forest · 523 Snowmist · 511 Terratone · 508 Musket · 507 Mocha · 280 White · 503 Eggshell · 462 Silver Lining · 805 Pewter · 204 Granite · 702 Low Gloss Brown · 411 Cottage Red · 470 Midnight Blue · 467 Evening Shade · 468 Fawn · 469 Fresh Canvas · 414 Ironstone · 605 Eldridge Gray · 606 Cozy Cottage · 827 Champagne · 809 Wicker · 177 Sandy Beige · 819 Herringbone · 509 Norwood

Plus 000 Mill on many items. Availability varies by item.

VERIFIED ROOFING & SIDING × MULE-HIDE & VERSICO

Low-slope roofing: TPO & EPDM

For porches, flat additions, dormers and other roofs too flat for shingles. Both brands offer TPO (heat-welded seams) and EPDM (rubber).

	Mule-Hide TPO	Versico VersiWeld TPO	Mule-Hide Self-Adhering EPDM	Versico VersiGard EPDM
Thickness	45, 60, 80 mil	45, 60, 80 mil "Plus"	60 mil	White: 60 & 90 mil; 60 mil reinforced; 60 mil QA self-adhered
Roll widths	4', 6', 8', 10', 12', 16' × 100'	Perimeter 4', 6'; field 8', 10', 12', 16'	10' × 100', 10' × 50', 5' × 40'	—
Colors	White, gray, tan; Colorway: Medium Bronze, Patina Green, Rock Brown, Slate Gray, Terra Cotta	White, gray, tan; special: Slate Gray, Medium Bronze, Rock Brown, Terra Cotta, Patina Green	Black, white-on-black	White (black also offered)
Attachment	Mechanically attached, fully adhered, ballasted; FleeceBack; self-adhering TPO	Fully adhered, mechanically attached, induction-welded	Self-adhered (factory adhesive), 3" factory seam tape	Adhered; White Peel & Stick accessories
Warranty	Material warranty on residential; system warranties up to 30 yr with a Warranty-Eligible contractor	80-mil special colors limited to 20 yr; color fade not covered	Up to 20 yr	—

TPO installation (mechanically attached)

1. Confirm the deck holds fasteners; remove wet insulation and make sure the roof drains (no ponding after 48 hours).
2. Clean the deck, fill gaps over 1/4", and install wood nailers at the edges.
3. Screw down insulation boards with staggered joints, tapered to drains where needed.
4. Unroll the TPO, let it relax 15–30 minutes, and lap sheets 5-1/2" at sides and 3" at ends.
5. Fasten in the laps with seam plates; add perimeter sheets and extra fasteners at edges and corners.
6. Hot-air weld every seam with a robotic welder, then probe every seam.
7. Flash walls and curbs (at least 8" up), install drains and edge metal, seal cut edges.

Self-adhering EPDM installation

1. Prepare the deck and insulation as for TPO (steps 1–3).
2. Unroll Mule-Hide SA EPDM; the factory adhesive means no separate bonding adhesive.
3. Peel the release liner and roll the sheet into place.
4. Join sheets with the 3" factory seam tape.
5. Flash curbs and parapets with SA EPDM flashing, then install edge metal.

Which one?

For most Michigan homes we quote 60 mil mechanically attached TPO or Mule-Hide self-adhering EPDM. White and light TPO reflect summer heat; EPDM is a proven rubber roof with fewer heat-welded seams.

VERIFIED ROOFING & SIDING × VELUX

VELUX skylights

Deck-mounted skylights for sloped roofs and curb-mounted units for low slopes. We replace skylights during a re-roof so the new flashing ties into the new roof.

Model	Type	Mount	Best for
FS	Fixed (no opening)	Deck	Daylight in halls, stairwells, vaulted ceilings
VS	Manual venting	Deck	Reachable ceilings, fresh air
VSS	Solar powered "Fresh Air" venting, remote control	Deck	High ceilings, kitchens and baths
FCM	Fixed	Curb	Low-slope roofs and existing curbs
VCM	Venting	Curb	Low-slope roofs needing ventilation

Deck-mount sizes (FS, VS, VSS)

Size code	Outside frame	Rough opening
C01	21-1/2" × 27-3/8"	21" × 26-7/8"
C04	21-1/2" × 38-3/8"	21" × 37-7/8"
C06	21-1/2" × 46-1/4"	21" × 45-3/4"
C08	21-1/2" × 54-15/16"	21" × 54-7/16"
M02	30-9/16" × 30-1/2"	30-1/16" × 30"
M04	30-9/16" × 38-3/8"	30-1/16" × 37-7/8"
M06	30-9/16" × 46-1/4"	30-1/16" × 45-3/4"
M08	30-9/16" × 54-15/16"	30-1/16" × 54-7/16"
S01	44-3/4" × 27-3/8"	44-1/4" × 26-7/8"
S06	44-3/4" × 46-1/4"	44-1/4" × 45-3/4"

FS also comes in A06, C12, D26 and D06.

Curb-mount sizes (inside curb)

FCM and VCM: 2222 (22-1/2" × 22-1/2"), 2234 (22-1/2" × 34-1/2"), 2246 (22-1/2" × 46-1/2"), 3030, 3046, 3434, 4646.
FCM only: 1943, 2230, 2270, 2347, 3055, 3171, 3422, 3446, 4622, 4630, 4672.

✓Warranty highlights

- 10-year installation warranty (defects in workmanship or materials related to installation).
- 10-year product warranty: frame, flashing, seals and roof integration.
- 20-year glass warranty against seal failure.
- 5-year warranty on shades and controls.
- Hail damage is covered only on laminated glass.

Installation process

1. Confirm size and placement between rafters; protect the interior below.
2. Remove the old unit or cut and frame the new rough opening.
3. Set the skylight square on the deck and fasten it.
4. Seal the frame with underlayment and install the matching VELUX flashing kit, integrated with the new shingles.
5. Finish the interior light shaft, test operation (venting models) and clean up.

General sequence; VELUX installation instructions govern each unit.

VERIFIED
— Roofing & Siding —

Get a free estimate at verifiedroofs.com

Based in Shelby Township, serving Macomb, Oakland, St. Clair, Sanilac, Tuscola and Lapeer counties, with projects up to 150 miles away.

CALL	VISIT	LICENSE
(586) 202-0793	**verifiedroofs.com**	**MI Residential Builder #262600903**

Roofing · Siding · Stone · Windows · Gutters
Measured, photographed and priced line by line. Tear-off, installation, cleanup and disposal included.

Verified Roofing & Siding · Shelby Township, Michigan · Michigan Residential Builder License #262600903 · Verifeyed Home Improvement LLC

Product specifications, dimensions, colors and warranty information are summarized from manufacturer literature as of 2025–2026 and may change without notice. Colors vary by region and production run, and printed or on-screen colors are not exact: select from physical samples. Warranty summaries are highlights only; the manufacturer's written warranty governs coverage, and some warranties require registration, specific accessories or a certified installer. Installation summaries describe the manufacturers' sequences for homeowner understanding and are not installation instructions. Product availability is confirmed at the time of order.

All trademarks and logos belong to their respective owners. They are used only to identify the products Verified Roofing & Siding installs and do not imply endorsement.