VERIFIED
Roofing & Siding

Siding & Stone Catalog 2026

Fiber cement · Composite · Vinyl · Steel · Yakisugi · Stone veneer

The manufacturer product lines we install for homeowners across Macomb, Oakland, St. Clair, Sanilac, Tuscola and Lapeer counties: specs, colors, accessories, warranty highlights and how each one goes on your home.

BRANDS WE INSTALL

James Hardie · NICHIHA · LP SmartSide TRIM & SIDING · Alside Exterior Building Products · ROYAL Siding · MASTIC by Ply Gem · certainteed SAINT-GOBAIN · QE QUALITY EDGE · NAKAMOTO FORESTRY · VERSETTA STONE · GenStone · AFFINITY STONE SIDING · Tando COMPOSITES

WELCOME

How we work

Every Verified project starts with facts about your home, not a guess. You get a written, line-by-line proposal you can compare, and the same crew standards on every job.

1

Measured

We measure every roof plane, wall, opening and run of gutter, so quantities on your proposal match your house.

2

Photographed

We photograph existing conditions (decking, flashing, siding, trim, windows) and share what we find.

3

Priced line by line

Materials, accessories and labor are listed item by item. No lump sums, no surprises.

4

Everything included

Tear-off, installation, job-site cleanup and disposal of old material are part of every project.

Service area. Based in Shelby Township, serving Macomb, Oakland, St. Clair, Sanilac, Tuscola and Lapeer counties, with projects up to 150 miles away.

Using this catalog. Each brand page lists product lines, sizes and coverage, color names, matching trims and accessories, warranty highlights and the manufacturer's installation sequence in plain language. Pricing is quoted per project by your Verified rep. Colors are listed by name only. Ask for physical samples, since printed and on-screen colors are not accurate.

Contents

Siding 3
- Siding materials at a glance 3
- James Hardie 4
- Nichiha 6
- Composite siding: LP SmartSide & Alside Ascend 7
  - LP SmartSide 7
  - Alside Ascend 8
- Vinyl siding overview 9
- Royal & Mastic vinyl 10
- CertainTeed vinyl 11
- Alside vinyl 12
- Vesta steel siding (Quality Edge) 13
- Nakamoto yakisugi 14
- Soffit & fascia 15

Stone veneer 16
- Versetta Stone & GenStone 16
- TandoStone & Affinity Stone 17

SECTION 02

02 Siding

Fiber cement, composite (LP SmartSide and Alside Ascend), vinyl, insulated vinyl, steel and charred-wood yakisugi, plus matching trim, soffit and fascia. Every siding job includes house wrap and flashing at openings as specified by the manufacturer.

Siding materials at a glance

Material	Brands in this catalog	Look & feel	Warranty headline
Fiber cement	James Hardie, Nichiha	Lap, panel, shingle and architectural panels; factory color or primed	Hardie 30-yr substrate / 15-yr ColorPlus; Nichiha 15 / 15 yr
Composite siding	LP SmartSide (engineered wood), Alside Ascend (glass-reinforced polymer + foam)	LP: deep cedar texture, 16 ft lap. Ascend: factory color, no painting, R-2.0 on 7" plank	LP 5/50-yr substrate + 15-yr ExpertFinish; Ascend lifetime limited (original owner)
Vinyl	Royal, Mastic, CertainTeed, Alside	Clapboard, Dutch lap, board & batten, shakes; widest color range	Lifetime limited (varies by brand and line)
Insulated vinyl	Alside Prodigy (and others)	Foam-backed, rigid panels; added R-value	Lifetime limited
Steel	Quality Edge Vesta	5" plank, solid and woodgrain finishes; horizontal or vertical	Lifetime limited
Yakisugi	Nakamoto Forestry	Japanese charred cypress-family wood, natural patina	25-yr limited on acrylic finish
Stone veneer panels	Versetta, GenStone, Affinity, TandoStone	Ledgestone and stacked-stone accents, no mortar	See Section 03

What's on every siding proposal

Wall prep

- Removal and disposal of old siding
- Sheathing repairs where needed
- House wrap / weather barrier with taped seams

Openings & trim

- Window and door flashing
- Corner, window and door trim
- J-channel, starter, drip cap per system

Finish

- Soffit, fascia wrap and vents
- Sealant and touch-up per manufacturer
- Cleanup, nail sweep, disposal

Install summaries on the following pages describe each manufacturer's sequence so you know what to expect. They are not installation instructions.

VERIFIED ROOFING & SIDING × JAMES HARDIE

James Hardie fiber cement siding

Hardie's HZ5 product line is engineered for northern climates like Michigan's freeze-thaw cycles. Choose factory-finished ColorPlus (Statement Collection) or primed boards painted on site.

HardiePlank lap siding (5/16" thick × 12 ft)

Plank width	Exposure	Sq ft / piece	Pieces / square
5.25"	4"	4.00	25.0
6.25"	5"	5.00	20.0
7.25"	6"	6.00	16.7
8.25"	7"	7.00	14.3
9.25"	8"	8.00	12.5
12"	10.75"	10.75	9.3

Exposure = width minus the 1-1/4" minimum lap. Coverage excludes waste. Textures: Smooth, Select Cedarmill, Beaded Smooth, Beaded Select Cedarmill (Beaded is 8.25" at 7" exposure).

HardieShingle panels (1/4" × 48" wide)

Panel	Size	Exposure	Pcs / sq
Straight Edge	48" × 14"	5"	60
Straight Edge	48" × 15.25"	7"	43
Staggered Edge	48" × 15.25"	6"	50

HardiePanel vertical siding

Size	5/16" × 4 ft × 8, 9 or 10 ft (32 / 36 / 40 sq ft)
Textures	Smooth, Select Cedarmill, Stucco, Sierra 8
Board & batten	Pair with HardieTrim Batten, 3/4" × 2.5" × 12 ft

Hardie Artisan (5/8" thick, primed, smooth)

Profile	Width	Exposure
Lap	7.25" / 8.25"	—
V-Groove	8.25"	7"
Shiplap	10.25"	9"
Square Channel	10.25"	9"

Lock-joint system with mitered corners; 12 ft lengths.

HardieTrim, batten & soffit (12 ft)

HardieTrim 4/4	3/4" thick; 3.5", 5.5", 7.25", 9.25", 11.25" wide
HardieTrim 5/4	1" thick; same widths plus 4.5"
HardieSoffit	1/4"; vented and non-vented; 12" × 12 ft, 16" × 12 ft, 24" × 8 ft

Weather barrier, flashing & finishing supplies

Item	Size / rule
Hardie Weather Barrier (11 mil)	Rolls 3' × 100', 9' × 100', 9' × 150'; seams taped with Hardie Seam Tape
Hardie Pro-Flashing	75 ft rolls, 4", 6" or 9" wide, for window and door openings
ColorPlus touch-up kit	About 1 kit per 4,000 sq ft of siding or 1,600 sq ft of trim
OSI QUAD MAX color-matched caulk	About 18–20 linear ft per tube

VERIFIED ROOFING & SIDING × JAMES HARDIE

James Hardie colors, trims & warranty

STATEMENT COLLECTION (COLORPLUS) · 19 COLORS AVAILABLE IN MICHIGAN

Arctic White · Cobble Stone · Navajo Beige · Khaki Brown · Timber Bark · Rich Espresso · Mountain Sage · Gray Slate · Aged Pewter · Night Gray · Evening Blue · Deep Ocean · Boothbay Blue · Pearl Gray · Monterey Taupe · Light Mist · Iron Gray · Countrylane Red · Midnight Black

Hardie's Michigan, Chicago & Ohio availability guide lists all 19. Not every size and texture comes in every color. Iron Gray is Hardie's 2026 Color of the Year. Dream Collection: nearly 700 made-to-order ColorPlus colors (longer lead time).

Matching trims

- HardieTrim boards for corners, frieze, columns, window and door surrounds.
- HardieTrim Batten (Smooth or Rustic Grain) for board & batten.
- HardieSoffit, vented and non-vented.
- Architectural Metal Trim: J, corner and transition profiles.
- Trim and soffit colors vary by region; confirmed at your color selection.

Accessories

- Hardie Weather Barrier (11 mil) with Seam Tape.
- Pro-Flashing (20 mil) and Flex Flashing (60 mil) at openings.
- Joint flashing behind every butt joint.
- Color-matched OSI QUAD MAX caulk; ColorPlus touch-up kits.

✓ Warranty highlights

- Siding, trim and soffit: 30-year limited, non-prorated, transferable.
- ColorPlus finish: 15-year limited.

Installation process

1. Remove old siding, repair sheathing, and install Hardie Weather Barrier with taped seams.
2. Flash windows and doors with Pro-Flashing / Flex Flashing.
3. Install HardieTrim at corners, windows, doors and frieze.
4. Fasten a 1-1/4" starter strip at the base.
5. Blind-nail each plank into every stud (24" o.c. max) with at least a 1-1/4" overlap.
6. Place joint flashing behind every butt joint (required for ColorPlus, not caulked), off studs and staggered.
7. Finish with color-matched caulk at trim and touch up with the ColorPlus kit.

VERIFIED ROOFING & SIDING × NICHIHA

Nichiha architectural wall panels (AWP)

Large fiber cement panels with wood, masonry, brick and modern textures. Panels hang on hidden Ultimate Clips, so there are no face nails, and the clip system creates a built-in rainscreen gap.

Format	Size	Coverage	Pack	Orientation
AWP 1818	17-7/8" × 71-9/16"	8.88 sq ft / panel	2 panels (17.76 sq ft)	Horizontal only
AWP 3030	17-7/8" × 119-5/16"	14.81 sq ft / panel	2 panels (29.62 sq ft)	Horizontal or vertical

Most lines are 5/8" thick; SandStone, VintageBrick and RiftSawn are 3/4". Shiplap edges: exposed and nominal coverage are the same.

Series	Line (format)	Colors
Wood	VintageWood (1818, 3030)	Bark, Cedar, Redwood, Ash, Spruce
Wood	RoughSawn (3030)	Espresso, Tobacco, Smoke
Wood	RiftSawn (1818) · Natura (1818)	Pecan, Chestnut · Rustic White
Masonry	SandStone (1818)	Autumn Brown, Parchment, Desert Beige, Dust, Gentle Gray, Misty Gray
Brick	CanyonBrick · ModernBrick · PlymouthBrick	Shale Brown · Midnight · Crimson
Brick	VintageBrick (1818)	Alexandria Buff, White Wash
Modern	ArchitecturalBlock · TuffBlock (1818)	Gray, Mocha, Tuscan · Steel, Bamboo, Walnut, Pewter, Taupe
Designer	Miraia (1818)	Snow, Glacier, Onyx (metal corners only)
Designer	Illumination (1818)	Warm White, Bay Blue, Cotton, Lava, Fog, Scarlet, Nickel, Russet, Graphite, Raven
Concrete	Corbosa (1818 horizontal)	Moondust, Shadow
Dimension	Ribbed · Novenary · Latura (3030)	Ivory, Indigo · Opal, White · Gray

Trims & accessories

- Metal trim (primed, clear anodized, powder coat or custom match): Corner Key, outside and inside corners, H-Mold, J-Mold.
- Prefinished fiber cement outside corners, 17-7/8" × 3-1/2" returns (not for Miraia).
- Ultimate Horizontal / Vertical Starter Track, Ultimate Clip II, corner clips, starter and overhang flashing, sealant backers.

✓ Warranty highlights

- Panels: 15-year limited.
- Factory finish: 15-year limited.
- Metal trim: 10 years (original purchaser).

Installation process

1. Install weather barrier and furring/rainscreen; set the starter track level.
2. Install starter and overhang flashing and metal corner / J trim sized to the panel.
3. Set each panel on the clip below and fasten Ultimate Clips at every stud (16" o.c. max framing).
4. Use corner clips with prefinished or metal corners; seal joints at trim with sealant over backer rod.
5. Vertical 3030: vertical starter track, H-mold at vertical joints, face screws every 16".

VERIFIED ROOFING & SIDING × LP SMARTSIDE

Composite siding: LP SmartSide engineered wood

Treated engineered wood strands with a deep cedar texture, in 16 ft lengths for fewer seams. Order primed (painted on site) or with LP's factory ExpertFinish color.

Product	Size	Coverage
38 Series lap 6" / 8" / 12"	3/8" nominal × 16 ft; 5.84 / 7.84 / 11.84" actual	Reveal 4-7/8" / 6-7/8" / 10-7/8" · 16 / 11 / 7 pcs per 100 sq ft
38 Series shakes (reversible)	about 48.6" × 12" nominal	44 pcs/sq at ~7" reveal; 31 pcs/sq at ~10" reveal
38 Series panel (8" o.c. grooves, smooth)	47.81" × 8, 9 or 10 ft	32 / 36 / 40 sq ft per panel
Nickel Gap lap	1/2" × 8" × 16 ft	7" reveal
Vertical siding 16"	15.94" × 16 ft	5 pcs per square
440 / 540 Series trim	4/4 (0.675") and 5/4 (0.970") × 16 ft; 1.5"–11.21" widths	by linear foot
Soffit (vented or closed)	12", 16" or 24" × 16 ft	Vented: 5 or 10 sq in per linear ft

LP coverage figures exclude waste. Board & batten is built from SmartSide panel plus SmartSide trim.

EXPERTFINISH · 16 STANDARD COLORS

Snowscape White · Sand Dunes · Desert Stone · Quarry Gray · Prairie Clay · Terra Brown · Harvest Honey · Timberland Suede · Garden Sage · Redwood Red · Tundra Gray · Summit Blue · Rapids Blue · Cavern Steel · Midnight Shadow · Abyss Black

EXPERTFINISH · NATURALS COLLECTION

Saffron Cedar · Bonsai Black

✓ Warranty highlights

- Substrate: 50 years. Years 1–5 include labor and material; years 6–50 material only, reduced 2.22% per year.
- ExpertFinish: 15-year finish warranty (chalk, peel, blister, crack, fade). Full coverage through year 5, then prorated 10% per year.
- Transfers once, to the next owner of the home.

Installation process

1. Install weather barrier and flashing; keep 6" clearance to grade and 1" to roofs, porches and patios.
2. Install trim first, then a 3/8" × 1-1/2" starter strip.
3. Blind-nail hot-dip galvanized nails into studs (16" o.c. max) with a 1" lap; heads snug, not countersunk.
4. Leave 3/16" at butt joints, staggered at least 16" and over studs (ExpertFinish shiplap ends need no caulk).
5. Seal every cut edge; touch up small nicks with the LP kit above 50°F.

Trims & accessories

- SmartSide 440 / 540 trim, soffit and fascia.
- Starter strip, ASTM C920 Class 25 sealant, Nickel Gap flashing.
- ExpertFinish touch-up kits.

VERIFIED ROOFING & SIDING × ALSIDE ASCEND

Composite siding: Alside Ascend

Ascend is Alside's composite cladding, made with its (GP)2 Technology: glass-reinforced polymer combined with graphite-infused polystyrene foam. It comes in a factory color, with no sealing, painting or joint caulking needed. The materials don't absorb moisture, so the panels won't rot, warp or swell. Each panel has a reinforced nail hem, a self-aligning stack lock and a sharp 3/4" projection.

Profile	Exposure	Length	Texture	Per carton	R-value
7" Plank (lap)	7" (8.25" wide)	12' 3"	Cedar mill or matte	14 planks = 1 square	2.0
5" Plank (lap)	5"	12'	Cedar mill	20 planks = 1 square	—
12" Board & Batten (vertical)	12" (10" board + 2" batten; 13.6" wide)	12'	Cedar mill or matte	8 panels = 0.96 square	1.6

Projection 3/4"; 7" plank butt height 3/8"; weight 0.31 lb/ft (7" plank) and 0.62 lb/ft (board & batten). R-values per ASTM C1363. Impact resistance over 35 in-lb (ASTM D4226). Class A fire (ASTM E84). Alside rates the reinforced nail hem for wind loads up to 180 mph. The 5" plank and the matte 7" plank are new for late 2026. "—" = not published.

COLORS · 21, IN EVERY PROFILE

Glacier White · Almond · Monterey Sand · Pebble · Canyon Drift · Flagship Brown · Rustic Timber · Dover Gray · Cape Cod Gray · Sterling Gray · Storm · Ageless Slate · Charcoal Smoke · Cast Iron · Laguna Blue · Harbor Blue · Midnight Blue · Riviera Dusk · Mountain Fern · Deep Moss · Fired Brick

Matching trims & accessories

- Ascend composite outside corner posts, 3-1/2" and 5-1/2" (all 21 colors).
- Ascend 5-1/2" H-trim for transitions and profile changes (all 21 colors).
- Ascend composite trim, 3-1/2" and 5-1/2" (Cape Cod Gray, Dover Gray, Flagship Brown, Glacier White, Monterey Sand, Pebble, Storm).
- Ascend J-channel, 1" face (all 21 colors); 2.5" galvanized steel starter strip; finish trim.
- Color-matched shakes and scallops: Traditional and Hand-Split shakes, Cape Cod shingle, scallops.
- Aluminum trim coil for fascia and window wraps in all 21 colors.

✓ Warranty highlights

- Lifetime limited warranty for the original owner while they own and live in the home, not prorated.
- Labor included for the first 5 years after installation.
- Lifetime limited fade protection: covers fading beyond 4 Hunter units (Delta E).
- Hail up to 1" in diameter (replacement material; homeowner's insurance is primary).
- Transfers once to the next owner as a 50-year limited, prorated material warranty.

Installation process

1. Install a water-resistive barrier and flash all openings; Ascend goes on a flat, solid wall.
2. Snap a level line and fasten the 2.5" steel starter strip every 8", at least 1/2" above grade.
3. Flash and hang outside corners, inside corners, J-channel, H-trim and window and door surrounds.
4. Seat each course in the stack lock below; leave 3/8" at corners and channels and check level every fifth course.
5. Overlap plank ends about 1/2" and stagger laps; fasten in slot centers with 1-1/4" penetration, never hard-nailed.
6. Finish under the soffit with receiving channel and finish trim. No joint caulk or touch-up paint.

Board & batten installs vertically, locked from the top down. Alside's installation guide governs.

VERIFIED ROOFING & SIDING

Vinyl siding: how the lines compare

Vinyl is low-maintenance and never needs paint. Thickness (gauge), panel rigidity, projection and color technology are what separate good, better and best lines.

Brand	Good	Better	Best / specialty
Royal	Residential	Estate, Crest	Haven (insulated), Woodland
Mastic	—	Carvedwood 44 (.044")	SolarDefense dark colors
CertainTeed	MainStreet (.042")	Monogram (.046")	Cedar Impressions shakes & shingles
Alside	Conquest (.040"), Coventry (.042")	Charter Oak (.046")	Prodigy insulated (.046", R-3.0)

Standard vinyl profiles and coverage

Profile	Length	Exposure	Pieces / carton	Coverage / carton
Double 4" clapboard	12'6"	8"	24	2 squares
Double 4-1/2" Dutch lap	12'1"	9"	22	2 squares
Double 5"	12'	10"	20	2 squares
Triple 3"	12'1"	9"	22	2 squares
Long-length Double 4"	16'8"	8"	18	2 squares
Insulated Double 6"	12'6"	12"	8	1 square
Board & batten	10'	7"	17	1 square

Industry-standard cartons confirmed across CertainTeed, Mastic and Royal literature. A square = 100 sq ft. Exact counts vary by line; your proposal uses the selected line's counts.

Matching vinyl trims

- Outside and inside corner posts (standard, woodgrain and wide designer corners).
- J-channel (1/2" to 1-1/4" for insulated siding), F-channel, undersill / finish trim.
- Window casings, lineals and crowns; starter strip; drip cap.
- Vinyl soffit (solid, center-vent, hidden-vent) and aluminum fascia wrap.

Installation process (all vinyl lines)

1. Prep a flat wall, install house wrap and flash windows and doors.
2. Install starter strip, corner posts, J-channel around openings, and undersill.
3. Hang panels loose: nails centered in the slots, a dime's width under the head, 16" o.c. max, 1-1/4" penetration.
4. Leave 1/4" expansion room in channels (3/8" in cold weather) and overlap panels 1"–1-1/4".
5. Finish with undersill trim, soffit and aluminum-wrapped fascia.

VERIFIED ROOFING & SIDING × ROYAL

Royal vinyl siding

Line	Profiles
Haven	D6, D7, D6 insulated, board & batten
Woodland	D4.5 Traditional and Designer, board & batten
Estate	D4, D5 Designer, D4.5 Designer, Beaded 6.5
Residential	D4, D4.5, D5, T3
Crest	D4, D4D, D45D, D5, D5D, D4 vertical, S8

COLORSCAPES TRADITIONAL

Vintage Cream · Sand · Brownstone · White · Heather · Wicker · Harvard Slate · Linen · Flagstone · Blue Gray · Sterling · Soft Maple · Silver Mist · Toasted Almond

COLORSCAPES PREMIUM

Cypress · Pebble Clay · Storm · Walnut · Tree Moss · Rockslide

COLORSCAPES DARK (CHROMATRIX)

Redwood · Shamrock · Midnight Surf · Granite · Heritage Blue · Ironstone · Riverway · Cocoa · Wedgewood · Weathered Gray · Marine Blue · Urban Bronze

Black and Musket Brown are soffit-only. Availability varies by line.

✓ **Warranty**

- Double Lifetime Warranty with full coverage to the second owner.

Royal trims: universal and designer outside corners (incl. 20 ft), inside corners, J-channels (1/2", 5/8", 3/4" flexible, 1-1/8" Haven), 3-1/2" and 5" window casings, integral window trim, window crown and sill, Haven starter, vinyl soffit (solid, hidden vent, full and center vent), matching trim coil.

VERIFIED ROOFING & SIDING × MASTIC

Mastic Carvedwood 44

Profiles: Double 4", Double 5", Dutch lap 4-1/2", Single 8" smooth, Triple 3" smooth. Accessories include utility, louvered and gable vents and Ventura Hidden Vent Soffit.

STANDARD COLORS (AS PRINTED BY MASTIC)

Almond · Cameo · Classic Cream · Colonial Yellow · Desert Sand · Linen · Sage · Sandtone · Silver Grey · Tuscan Olive · Victorian Grey · Wicker · White · Corn Silk · Everest · Harbor Grey · Pebblestone Clay · Scottish Thistle · Autumn Harvest · Bayou · Brunswick · Deep Granite · English Wedgewood · Lakeshore Fern · Misty Shadow · Modern Iron · Montana Suede · Quiet Willow · Rugged Canyon · Russet Red · Vintage Dublin

SOLARDEFENSE DARK COLORS

Alpine Forest · Brandy Wood · Deep Cavern · Natural Slate · Newport Bay · Red Brick · Rock Harbor · Whispering Timber · Woodland Retreat

✓ **Warranty**

- V.I.P. Limited Lifetime: defects, excessive fade and hail, for as long as you own the home; transferable.
- SolarDefense "No Fade, No Distortion Promise" on dark colors.

VERIFIED ROOFING & SIDING × CERTAINTEED

CertainTeed vinyl siding

Line	Profiles & lengths	Gauge / projection	Colors
Monogram	Double 4" clapboard (12'6", 16'8", 20', 25'); Double 5" clapboard (12'); Double 5" Dutchlap (12', 16')	.046" / 3/4"	40
MainStreet	Triple 3" brushed clapboard; Double 4" & 5" woodgrain clapboard and Dutchlap; Single 8" clapboard; Single 6-1/2" beaded; 12'–12'6"	.042" / 9/16" (5/8" some)	25
Cedar Impressions Sawmill Shingles	Individual 5" (exposures 4"–8"); Triple 5" (60" long)	1/2"–3/4" projection	39
Cedar Impressions Perfection Shingles	Double 7" Straight Edge (48"); Double 7" Staggered (73-1/2"); Single 7" (48")	3/4" projection	38
Cedar Impressions Perfection Shapes	Single 6-1/3" Scallop, Octagon, Half-Cove; 42" long	—	8
Cedar Impressions Rough-Split Shakes	Double 7" Straight Edge; Double 9" Staggered; 57" long	1" projection	16

MONOGRAM · PREMIUM BLENDS

Arbor · Weathered · Frontier · Natural · Driftwood · Cedar · Rustic Blend

MONOGRAM · SOLIDS AND DELUXE

Brownstone · Melrose · Autumn Red · Tuxedo · Slate · Espresso · Sable Brown · Sparrow · Spruce · Olive Grove · Forest · Midnight Blue · Deep Mineral · Pacific Blue · Wedgewood Blue · Flagstone · Smoky Gray · Charcoal Gray · Castle Stone · Granite Gray · Graystone · Sterling Gray · Oxford Blue · Seagrass · Cypress · Herringbone · Sandstone Beige · Desert Tan · Weathered Wood · Natural Clay · Savannah Wicker · Heritage Cream · Colonial White

Not every Monogram color comes in every profile; confirmed from CertainTeed's color chart.

MAINSTREET · 25 COLORS

Autumn Red · Sable Brown · Spruce · Forest · Pacific Blue · Wedgewood Blue · Flagstone · Charcoal Gray · Castle Stone · Granite Gray · Graystone · Sterling Gray · Oxford Blue · Seagrass · Cypress · Herringbone · Sandstone Beige · Desert Tan · Weathered Wood · Natural Clay · Savannah Wicker · Heritage Cream · Autumn Yellow · Snow · Colonial White

PERFECTION SHAPES · 8 COLORS

Autumn Red · Pacific Blue · Charcoal Gray · Sterling Gray · Cypress · Natural Clay · Savannah Wicker · Colonial White

Sawmill Shingles (39 colors) and Perfection Shingles (38) include Natural, Driftwood, Cedar and Rustic blends plus most Monogram solids.

ROUGH-SPLIT SHAKES · 16 COLORS

Autumn Red · Mountain Cedar · Sable Brown · Sparrow · Hearthstone · Spruce · Forest · Pacific Blue · Flagstone · Charcoal Gray · Granite Gray · Sterling Gray · Natural Clay · Savannah Wicker · Buckskin · Colonial White

✓ Warranty highlights

- Lifetime Limited Warranty on Monogram, MainStreet and Cedar Impressions.
- Monogram and MainStreet include PermaColor fade protection.

VERIFIED ROOFING & SIDING × ALSIDE

Alside vinyl siding

Four Alside vinyl lines, from the economy Conquest to the insulated Prodigy. Prodigy's rigid foam backing makes the wall flatter and adds R-value. For Alside's composite option, see Ascend in the composite siding pages.

Line	Profiles / length	Gauge	Colors
Prodigy (insulated)	Double 5" and Double 6"; 16'8"; up to 1-1/2" thick; R-3.0 (5") / R-2.6 (6")	.046"	22
Charter Oak	Double 4-1/2" clapboard and Dutch lap, oak grain; 12'1" (XL Grain and XL Matte in 16'8")	.046"	29 (XL Matte 15)
Coventry	Double 4" (12'6") and Double 5" (12') clapboard and Dutch lap; cedar grain	.042"	21
Conquest	Double 4-1/2" clapboard and Dutch lap; 12'1"	.040"	16

PRODIGY · 22 COLORS (ALSO IN CHARTER OAK)

Adobe Cream · Ageless Slate · Antique Parchment · Canyon Drift · Cape Cod Gray · Charcoal Smoke · Coastal Sage · Deep Moss · Glacier White · Harbor Blue · Juniper Ridge · Maple · Midnight Blue · Monterey Sand · Mountain Fern · Mystic Blue · Natural Linen · Platinum Gray · Sterling Gray · Storm · Tuscan Clay · Vintage Wicker

CHARTER OAK ONLY · 7 ADDITIONAL DARK COLORS (29 TOTAL)

Cast Iron · Deep Espresso · Fired Brick · Flagship Brown · Laguna Blue · Riviera Dusk · Rustic Timber

Coventry adds Canyon Clay (plus Cottage Yellow, Dune Grass, Sand Bar, Sea Mist on D5 clapboard); Conquest offers 16 of the core colors. Some colors are not available in all areas.

Matching vinyl trims & accessories

- 3" and 4" outside corner posts; inside corners.
- J-channel, 1/2" to 1-1/4" pockets (wide pockets for Prodigy), and WidePocket J.
- Finish / utility trim at windows and under soffits.
- Prodigy starter, or the 3" Easy Start starter strip for standard lines.
- Vinyl soffit and aluminum fascia wrap (see Soffit & fascia).

✓Warranty

- Limited Lifetime Warranty (excludes damage from faulty or improper installation). Full terms at alside.com.

Installation

Alside vinyl follows the vinyl installation sequence on the vinyl overview page: house wrap and flashing, starter and corner posts, panels hung loose in the nail slots with room to expand, then undersill trim, soffit and fascia.

VERIFIED ROOFING & SIDING × QUALITY EDGE

Vesta steel siding by Quality Edge

A single 5" steel plank (0.020" steel) that installs horizontally, vertically, or as soffit and porch ceiling. Kynar matte paint finishes resist fading and won't crack, warp or burn. Made in Walker, Michigan.

Finish	Length	Pieces / carton	Coverage
Solid colors	12 ft	10	1/2 square per carton (5.0 sq ft per plank)
HD3 woodgrain	8 ft	15	1/2 square per carton (3.33 sq ft per plank)

Vented versions come in the same lengths and counts. Two cartons cover one square.

SOLID COLORS · 11 (KYNAR MATTE)

Coal 463 · Silver Lining 462 · Sea Glass 465 · Ironstone 414 · Tourmaline 466 · Eggshell 503 · White 280 · Evening Shade 467 · Midnight Blue 470 · Fawn 468 · Fresh Canvas 469

HD3 WOODGRAIN · 6 (KYNAR 500 MATTE)

Dark Espresso 484 · Aged Walnut 485 · Autumn Thistle 480 · Gilded Grain 482 · Driftwood 481 · Sand Dollar 483

✓ Warranty highlights

- Lifetime Limited Warranty (details at QualityEdge.com/Warranties).

Matching steel trims

Accessory (0.016" steel)	Length
Plank starter strip	10 ft
Outside corner post (dual / single flange)	10 ft
Inside corner block	10 ft
J-channel (1/2" finish trim)	12 ft
H-channel	10 ft
Drip cap · L-flashing	10 ft
Brick ledge flashing / support trim	10 ft
Fascia 6" or 8" (standard / architectural)	12 ft / 10 ft
Trim coil	14.77" × 30 ft

Openings are trimmed with J-channel, utility trim and coil (no window lineal). Touch-up paint and saw blades also available.

Installation process

1. Install house wrap, then starter trim, corner posts and J/H channels.
2. Fasten planks at 16" o.c. (accessories at 12") with #11 electro-galvanized roofing nails or #8 zinc screws; never aluminum nails or staples.
3. Stack and interlock the 5" planks for a gap-free face, horizontal or vertical.
4. Add vented plank soffit and the fascia bracket system; touch up scratches.

VERIFIED ROOFING & SIDING × NAKAMOTO FORESTRY

Nakamoto Forestry yakisugi

Yakisugi (shou sugi ban) is Japanese wood siding preserved by charring. Nakamoto offers four surfaces, from deep char to planed, with finishes that range from "let it weather" to "hold the color."

Profile (9/16" siding)	Actual width	Coverage width	Sq ft / piece
1x6 Shiplap	5-11/16"	5-5/16"	5.33
1x6 S3S square edge	5-11/16"	full face	5.75
1x8 Shiplap	7-11/16"	7-5/16"	7.33
1x8 S3S square edge	7-11/16"	full face	7.75
5/4x8 S3S	7-11/16"	full face	7.75
5/4x5 S3S	4-3/4"	full face	4.75

Boards are 145-11/16" (12.14 ft) long. Nakamoto recommends a 15–25% overage, and sells in bundle increments.

Surface	Finishes and colors
Suyaki (deep char)	Unoiled; Tung Oil (Black)
Gendai (brushed char)	Unoiled; Linseed (Black, Brown, Light Gray, Dark Gray, Amber); Alkyd (Black, Brown, Light Gray, Dark Gray, Natural); Acrylic (Black); Weathering Stain (Silver)
Pika-Pika (planed, light char)	Unoiled; Linseed (Black, Brown, Light Gray, Dark Gray, Amber, Natural, White); Alkyd (Black, Brown, Light Gray, Dark Gray, White, Natural); Acrylic (Black)
Sugi (uncharred)	Unoiled; Weathering Stain (Silver)

How much will it change? (patina scale 0–10)

Acrylic	0 · holds color
Tung oil	1
Alkyd	3
Linseed	5
Weathering Stain	9
Unoiled Gendai / Sugi	10 · changes most

✓ Warranty highlights

- Acrylic finish: 25-year limited manufacturer warranty.

Installation process

1. Install weather barrier, then furring (at least 3/8" thick, 16" o.c. max) to create a vented rainscreen.
2. Install flashing and trim, leaving 1/4" clearance between boards and flashing or trim.
3. Fasten boards with 316 stainless ring-shank nails or trim-head screws, 2 per board at every furring crossing.
4. Keep a 3/16" shadow gap where the profile calls for one and 1/4" at board ends.
5. Choose a maintenance plan: none (unoiled), periodic recoat (linseed or alkyd), or rarely (acrylic).

VERIFIED ROOFING & SIDING × QUALITY EDGE, JAMES HARDIE, LP, ROYAL & MASTIC

Soffit & fascia

Soffit closes in the underside of your eaves and feeds fresh air to the attic; fascia is the face board the gutters hang on. We wrap fascia in aluminum trim coil and match soffit to your siding system.

VERIFIED ROOFING & SIDING × QUALITY EDGE

Quality Edge aluminum soffit

Soffit	Gauge / width	Vent options	Net free area
TruVent Hidden Vent	12" × 12 ft	Hidden vent	11.0
TruBead Jet 45	12" × 12 ft	Vented or solid	10.2
TruLine HP / TS	.019" (HP) / .016" (TS); 12" and 16" × 12 ft	Full, center or solid	5.9–19.6
Vesta Plank Soffit (steel)	5" plank; 8 and 12 ft	Vented	11.4 per panel

Q800 TuTech coating. Net free area (NFA) is the open vent area that feeds attic ventilation.

QUALITY EDGE SOFFIT COLORS

Evening Shade · Mocha · Clay · Cozy Cottage · Pewter · White · Forest · Desert Tan · Cottage Red · Snowmist · Silver Lining · Wicker · Musket · Eldridge Gray · Gray Dusk · Champagne · Norwood · Herringbone · Midnight Blue · Brown · Black · Ironstone · Fresh Canvas · Fawn · Eggshell · Terratone · Granite · Sandy Beige · Foothill Blue · Bennington Beige · Ripe Olive · Statuary Bronze · Thatch

Plus the Vesta HD3 woodgrains. Not every color comes in every profile.

Other soffit systems we install

System	Details
James Hardie HardieSoffit	Fiber cement, 1/4"; vented and non-vented; Smooth and Select Cedarmill; 12" × 12 ft, 16" × 12 ft, 24" × 8 ft
LP SmartSide soffit	Engineered wood, vented or closed; 12", 16", 24" × 16 ft; 5 or 10 sq in NFA per linear ft
Vinyl soffit (Royal, Mastic, CertainTeed)	Triple 4" (12" × 12 ft) and Double 5" / Triple 3-1/3" (10" × 12 ft); solid, center-vent, full-vent, hidden-vent and beaded
Royal aluminum Cedar Renditions	Woodgrain soffit: Timberline, Riverwood, Smokewood, Grey Oak, Amberwood, Charwood, Cedar Bark, with matching trim coil

Soffit & fascia installation

1. Inspect rafter tails and sub-fascia; replace rotted wood.
2. Install J-channel or F-channel at the wall and fascia lines.
3. Install soffit panels, using vented panels to meet the attic's intake ventilation needs.
4. Wrap fascia boards with brake-formed aluminum trim coil, then hang gutters.

SECTION 03

03 Stone veneer panels

Mechanically fastened panel systems: no mortar, lath or scratch coat. Use them for wainscot, accent walls, columns and full elevations, alongside any siding in this catalog.

VERIFIED ROOFING & SIDING × VERSETTA STONE

Versetta Stone

Item	Spec
Profiles	Ledgestone (rough-cut dry-stack or sandstone look); Tight-Cut (random ashlar, quarried limestone look)
Flat panel	36" × 8"; 2 sq ft per panel; 4 screws per panel
Universal corner	36" × 8" with finished edges; works for outside and inside corners, end walls and columns
Built-in features	Tongue-and-groove panels, embedded G-90 galvanized nail strip, nailing flange, pre-drilled weep holes, built-in 1/4" rain screen
Accessories	Wainscot cap/sill, J-channel and starter strip (10 ft); trim stone 36" × 3-1/2"; receptacle, light and large light boxes; 22" × 22" pier cap; screws

STONE COLORS (GRANITE PEAK, LUNAR DRIFT, GLEN CANYON NEW FOR 2025)

Northern Ash · Plum Creek · Mission Point · Sterling · Granite Peak · Lunar Drift · Glen Canyon

ACCESSORY COLORS

Taupe Stone · Grey Charcoal

✓ **Warranty highlights**

- 50-year limited warranty.
- Nail strip: 50-year corrosion warranty.

VERIFIED ROOFING & SIDING × GENSTONE

GenStone faux stone panels

Stacked-stone panel	42" L × 12" H; covers 41" × 11" (about 3.13 sq ft); 1.25" deep; 3 lb
Edges	1" shiplap on top and right edges
Corners	Matching 90° corners with the stagger built in
Ledger	42" × 3.5" cap that sheds water at the top of wainscot
Also	Brick and wood panel lines, columns and pillars, trim, caulk, paint kits, custom colors

STONE COLORS

Arctic Smoke · Coffee · Desert Sunrise · Iron Ore · Kenai · Keystone · Northern Slate · Stratford · Vanilla Bean

Lightweight polyurethane panels: measure, cut and attach. Cut edges are touched up with GenStone paint kits.

VERIFIED ROOFING & SIDING × TANDOSTONE

TandoStone composite stone

	Stacked Stone	Creek Ledgestone
Panel exposure	39.68" W × 18.25" H	40" W × 18.13" H
Per box	10 panels = 1/2 square (about 50 sq ft)	10 panels = 1/2 square (about 50 sq ft)
Corner	6.5" × 6.38" × 18.25" H; 6 per box (9.2 LF)	7.25" × 7.38" × 18.13" H; 5 per box (7.5 LF)

COLORS ACROSS BOTH PROFILES

Appalachian Ash · Arizona Sandstone · Bucks County Gray · Nordic Mist · Rocky Mountain Clay · Lewiston Crest · Tan · Pewter · Seaside Gray · Dark Brown · Chestnut Hills · Glacier Bay · Santa Fe · Sedona Bluff · Raven · White · Sable

Profile availability by color confirmed at selection.

Accessories

- Architectural Sill (30.13" W) and Sill Corner.
- 1-1/8" J-channel (12'6") and vinyl outside corner post (10').
- Universal Starter Strip (required); starter clips in every stone box.

VERIFIED ROOFING & SIDING × AFFINITY STONE

Affinity Stone panels

Profiles	Ridge Cut (2", 4", 6" courses); Cliff Ledge (1.5" and 3" courses); stones 3.5"–15" long
Box	5 pieces, 10 sq ft, 135 lb
Corners	Outside corners (textured edges); flats are used at inside corners
Accessories	4" × 96" starter strip; wainscot cap (Gray, Charcoal, Ivory, Sandstone); 22" column cap; column kits for 4x4 to 8x8 posts; metal edge trim (Black, Gray, Stone, Clay)

✓Warranty highlights

- 50-year limited warranty against blistering, peeling, delamination and excessive cracking from manufacturing defects.
- Material only, prorated and non-transferable; fade from weathering is excluded.
- Keep de-icing salt and standing water off the panels; no paint, sealers or power washing.

COLORS

Aspen · Cambridge · Redwood · Glacier · Yukon

Installation process (all stone panel systems)

1. Prepare the wall: weather-resistive barrier over sheathing, old siding removed where needed.
2. Plan the layout and count flat panels, corners, sills and outlet / light boxes.
3. Install the starter strip level at the base (kept above grade and splash zones) and J-channel at edges and openings.
4. Set corners first, then run flat panels out from the corners; each interlocks and is screwed through its flange.
5. Stagger seams, cut around windows, doors and utilities, and add receptacle and light boxes as you go.
6. Cap the top with a sill, ledger or wainscot cap so water runs off; seal where the manufacturer calls for it.
7. Walk through: check weep holes and drainage, touch up cut edges.

General sequence drawn from the four manufacturers' system features; each brand's guide governs.

VERIFIED
— Roofing & Siding —

Get a free estimate at verifiedroofs.com

Based in Shelby Township, serving Macomb, Oakland, St. Clair, Sanilac, Tuscola and Lapeer counties, with projects up to 150 miles away.

CALL	VISIT	LICENSE
(586) 202-0793	**verifiedroofs.com**	**MI Residential Builder #262600903**

Roofing · Siding · Stone · Windows · Gutters
Measured, photographed and priced line by line. Tear-off, installation, cleanup and disposal included.

Verified Roofing & Siding · Shelby Township, Michigan · Michigan Residential Builder License #262600903 · Verifeyed Home Improvement LLC

Product specifications, dimensions, colors and warranty information are summarized from manufacturer literature as of 2025–2026 and may change without notice. Colors vary by region and production run, and printed or on-screen colors are not exact: select from physical samples. Warranty summaries are highlights only; the manufacturer's written warranty governs coverage, and some warranties require registration, specific accessories or a certified installer. Installation summaries describe the manufacturers' sequences for homeowner understanding and are not installation instructions. Product availability is confirmed at the time of order.

All trademarks and logos belong to their respective owners. They are used only to identify the products Verified Roofing & Siding installs and do not imply endorsement.